

MODEL 9113

WIRELESS Ndx ADSL2+ GATEWAY

WIRELESS
BROADBAND SOLUTIONS

Maximize the performance and flexibility of your ADSL broadband connection with the USRobotics **Wireless Ndx ADSL2+ Gateway**. This powerful multi-function device integrates the latest ADSL and **Ndx** wireless technologies for a complete home or small business broadband network. Featuring SecureEZSetup™ for simple and fast installation and security configuration, and exclusive **Ndx** wireless technology, the gateway delivers wireless speeds up to 270 Mbps* and up to 5 times greater range than standard 802.11g. It is designed for total home/small business coverage and optimal performance. A full complement of security capabilities and an integrated USB print server provide for confident, flexible, and high-performance wireless networking, and support for ADSL2+ assures you optimal ADSL speeds up to 24 Mbps†.

USRobotics®

Advanced ADSL connectivity & powerful wireless networking in one simple solution



Five Products in One

- Wireless Access Point - 802.11g/802.11b compatible with **Ndx** acceleration technology
- 4-Port Ethernet Switch - Connect up to 4 Ethernet devices right out of the box
- Broadband Router - Support up to 253 users (with additional Ethernet hubs/switches)
- Print Server - Share a USB printer over the network‡
- Stateful Packet Inspection (SPI) Firewall – Protect your network from hackers

Ndx Technology

- Incredible Range – 500% greater than standard 802.11g
- Fantastic Speed – Up to 270 Mbps performance
- Strong Security – Industry leading network and wireless security
- Astounding Simplicity – Seamlessly install gateway, if appropriate an **Ndx** wireless adapter, and set up security

Excellent Security

- Full suite of wireless security features including Wi-Fi Protected Access 2 (WPA2), WPA, 64/128-Bit WEP encryption, and 802.1x Authentication
- For Businesses, support for IPSec Termination and VPN pass-through (IPSec, PPTP & L2TP)
- For Home, Parental Control to limit Internet access

Advanced ADSL Technology

- Support for the latest ADSL standards including ADSL2 and ADSL2+; for advanced speeds up to 24 Mbps
- ATM QoS support for high quality Video over DSL (Bind ATM traffic to any Ethernet port)

Broad Compatibility


- Works with 802.11g/b and accelerated wireless technology

Easy to Install and Use

- Simple installation with USRobotics' EasyConfigurator utility



Secure
Easy
Setup™



WIRELESS **N_{dx}** ADSL2+ GATEWAY



MODEL 9113 SPECIFICATIONS & STANDARDS

General

- Ndx, MAXg, 802.11g/b
- 802.11d (Bridge and Bridge Filtering)
- 802.11e (QoS)
- WMM Quality of Service (QoS) support

ADSL

- ADSL2 (ITU-T G.992.3/ADSL2+ (ITU-T G.992.5): up to 24 Mbps[†]
- S=1/2 for up to 12 Mbps[†]
- Supports full-rate G.DMT (ITU-T G.992.1) and T1.413 Issue 2 ADSL: up to 8 Mbps downstream and up to 1 Mbps upstream[†]
- Supports G.lite (ITU-T G.992.2) ADSL: up to 1.5 Mbps downstream and up to 512 Kbps upstream[†]
- Supports DSL handshaking (ITU-T G.994.1)
- RFC 2516 PPP over Ethernet (Client)
- RFC 2364 PPP over ATM
- RFC 2684 (formerly 1483) Multi-protocol over ATM (Bridged and Routed)
- Annex A or B (ITU & ETSI), Annex L & Annex M
- Multicast video streaming

Router

- DHCP Server (LAN), DHCP Client (WAN)
- Supports up to 253 users

Security

- Stateful Packet Inspection (SPI) firewall
- PPP Authentication: PAP, CHAP & MSCHAP
- VPN pass-through: IPSec, PPTP & L2TP
- Wireless Protected Access 2 (WPA2)/802.11i
- AES Encryption
- 64/128-Bit WEP Encryption
- WPA, TKIP
- 802.1x Authentication

Physical

- 10 LEDs: Power, Wireless, SecureEZSetup, WAN IP, ADSL, LAN (4), Printer
- Annex A version: 4 RJ-45 Ports, 1 RJ-11 Port (4 LAN, 1 WAN)
- Annex B version: 5 RJ-45 Ports (4 LAN, 1 WAN)
- USB 1.1/2.0 port (for attaching USB printer)
- 3 Reverse SMA 2 dBi Antennas (one with cable and desktop base)

Frequency Band

- 2400 ~ 2483.5 MHz for ETSI

ENVIRONMENTAL

- **Temperature:** Operating Temperature conditions: 0 to 50 degrees C, Non-Operating Temperature conditions: -20 to 70 degrees C
- **Humidity:** Operating Humidity conditions: 95% non-condensing, Non-Operating Humidity conditions: 95% non-condensing

Operating Channels

- 13 channels for EMEA ETSI

Regulatory

- EMI & Safety - CE Class B

Package Dimensions/Weight

- 11 x 3.8 x 8.9 in (27.94 x 9.66 x 22.6 cm)
- 3 lb (1.362 kg)

Product Dimensions/Weight

- 5.5 x 9.2 x 1.6 in (13.97 x 23.36 x 4.06 cm)
- 1 lb (0.454 kg)

Languages

- **Retail Box:** English, French, Italian, German, Dutch, Spanish, Turkish
- **Installation Guide:** English, French, Italian, German, Dutch, Spanish, Turkish
- **CD ROM User Guide:** English, French, Italian, German, Spanish, Arabic, Dutch, Greek, Turkish

Package Contents

- USRobotics Ndx ADSL2+ Gateway
- 2 Reverse SMA 2 dBi Antennas (female)
- 1 Reverse SMA 2 dBi Cabled Desktop Antenna
- Power Supply
- Ethernet Cable
- Phone Cable and/or Microfilter
- Quick Installation Guide
- CD-ROM with User Manual

Minimum System Requirements

- HTML configuration is supported by any computer that supports TCP/IP and HTML Web Browser (4.01 specification or greater)
- Ethernet networking requires computers with an installed network interface card (NIC)
- Print Server works with any printer that supports a page description language (e.g. PostScript, PCL, etc.)
- CD-ROM drive

Warranty

- Two-year limited manufacturer warranty from date of purchase

* Actual performance may vary depending on operating environment and distance between networked devices.

† ADSL speeds depend on telephone company/ISP service offerings and distance from telco central office.

‡ Works with USB printers that support a page description language (e.g. PostScript, PCL, etc.).

Annex A model: For connection to the Public Switched Telephone Network (PSTN)
Annex B model: For connection to the Integrated Services Digital Network (ISDN)

USRobotics®

CE0560!    